

CHECKER

Checker matting

03/07/2014

STANDARD MATTING

FEATURES

Checked pattern.

ADVANTAGES

- ▶ Non-slippery
- ▶ Thermal and acoustic insulation
- ▶ Noise, vibration, and cold propagation reduction
- ▶ Very good wear and tear resistance
- ▶ Excellent walking and standing comfort
- ▶ Easy to clean and low maintenance

BENEFITS

- ▶ Safety
- ▶ Comfort
- ▶ Economy

APPLICATIONS

Suitable for industrial site.

Indoor installations.

Warehouses, aisles, locker rooms, machine or heavy equipment fronts, with no specific chemical or mechanical requirements.

www.trelleborg.com/elastomerlaminates

MECHANICAL, PHYSICAL AND CHEMICAL PROPERTIES

| | Measured characteristics | Standard | Value | |
|------------|---------------------------|------------|--------|-----------------|
| MECHANICAL | Rubber compound | | SBR | |
| | Hardness | ASTM D2240 | 70 ± 5 | Shore A |
| | Abrasion resistance (5 N) | ISO 4649 | ≤ 250 | mm ³ |

PROFILE



PATTERN



Checker (MK)

DIMENSIONS

| Colour | Thickness (mm) | | Width (mm) | | Length (m) | | Weight (kg/m ²) | Pattern |
|--------|----------------|-------|------------|-------|------------|-------|-----------------------------|---------|
| ● | 3 | ± 0.3 | 1400 | ± 2 % | 10 | ± 2 % | 3.9 | MK |

IDENTIFICATION

| | |
|-----------|---|
| Branding | Without. |
| Back face | Fabric impression. |
| Packaging | Rolled on cardboard tube Ø 80 mm. |
| Wrapping | Black polyethylene film. |
| Labelling | Self-adhesive label indicating product name, dimensions, area in m ² , nominal weight, and product code to allow product traceability. |