



RING Honeycomb matting

03/07/2014

STANDARD MATTING

FEATURES

Honeycomb design.
Non-slip surface.
Open or closed.

ADVANTAGES

- ▶ Non-slippery
- ▶ Thermal and acoustic insulation
- ▶ Noise, vibration, and cold propagation reduction
- ▶ High damping and insulation power
- ▶ Reduces tiredness and helps to increase productivity
- ▶ Mud-removing
- ▶ Easy to take up and clean
- ▶ Suitable to be used with wet and cold floors

BENEFITS

- ▶ Safety
- ▶ Comfort
- ▶ Performance
- ▶ Economy
- ▶ Cleanliness

APPLICATIONS

Heavy transit areas.

Floor mats at work stations.

The open variety has been developed for self-draining, and is especially appropriate for swimming pools, health resorts, beach areas, or any place where drainage is required.

www.trelleborg.com/elastomerlaminates


MECHANICAL, PHYSICAL AND CHEMICAL PROPERTIES

	Measured characteristics	Standard	Value	
MECHANICAL				
	Rubber compound		SBR	
	Hardness	ASTM D2240	70 ± 5	Shore A
	Abrasion resistance (5 N)	ISO 4649	≤ 250	mm ³

PROFILE



Honeycomb (MH) open



Honeycomb (MH) closed

DIMENSIONS

Colour	Thickness (mm)		Width (mm)		Length (m)		Weight (kg/m ²)	Pattern
●	14	± 1	1000	± 2 %	1.8	± 2 %	8	MH open
●	22	± 1.75	800	± 2 %	1.2	± 2 %	15	MH open
●	22	± 1.75	1000	± 2 %	1.5	± 2 %	15	MH open
●	14	± 1	1000	± 2 %	1.8	± 2 %	9.5	MH closed

IDENTIFICATION

Branding	Without.
Back face	With support pivot pins.
Packaging	Laid onto the pallet.
Wrapping	Black polyethylene film.
Labelling	Self-adhesive label indicating product name, dimensions, area in m ² , nominal weight, and product code to allow product traceability.